

QUICKTIE™ EPOXY – QE-1

PRODUCT FEATURES:

QuickTie™ QE-1 adhesives are an injectable two-component adhesive, tested to meet IBC requirements for both cracked and uncracked concrete applications. QE-1 adhesives are used for multiple anchoring systems, including QuickTie™ cables, fractional and metric threaded rod and rebar applications.

CODE COMPLIANCE:

ICC-ESR 4467



ESR-4467
(QE-1 Adhesive
Anchoring System)

Part No.	Description	Standard Box Package
QE-1*	Quick Set Anchoring Epoxy - 19.8 oz	6
QE-1TL**	High Performance Manual Tool (19.8 oz)	1
1BSH	Epoxy Hole Cleanout Brush	1

* One mixing nozzle is packaged with each cartridge. QE-1 & QE-2 mixing nozzles must be used to ensure complete and proper mixing of the adhesive.

** For pneumatic or cordless, battery operated dispensing tools, contact QuickTie™ for ordering information.



QE-1 (19.8 OZ.)



QE-1TL (19.8 OZ.)



1BSH




QE-1 NOZZLE

QE-1 ALLOWABLE TENSION VALUES FOR QUICKTIE™ SYSTEMS (QT)

Cable Type	Cable Diameter	Minimum Edge Distance, c_{a1}	Minimum End Distance, c_{a2}	Minimum Embedment Depth, h_{ef}	Allowable QT System Tension Loads ^{1,2,3}
	(in.)	(in.)	(in.)	(in.)	(lb)
QTB (Blue)	3/16	2-1/4	6	4	1,910
QTG (Green)	1/4	2-1/4	6	4	3,180
QTO (Orange)	5/16	3	6	6-5/8	4,455
QTR (Red)	3/8	3-1/2	6	8-1/8	6,545

NOTES:

- Allowable QT System tension loads are based on test results with cables installed in uncracked concrete and no supplementary reinforcement.
- Minimum 28-day concrete compressive strength is 2,500 psi.



QE-1 & QE-2 STRENGTH DESIGN AND ALLOWABLE STRESS DESIGN TENSION VALUES FOR THREADED RODS¹⁻⁸

Rod Diameter, D (in.)	Slab Thickness, h _s (in.)	Embed Depth, h _{ef} (in.)	End Distance, c _{a2} (in.)	Critical Edge Distance, c _{ac} (in.)	Concrete	ALLOWABLE TENSION (LB) - 2,500 PSI CONCRETE												
						At Edge Distance, c _{a1}												
						1-3/4"	2"	2-1/4"	2-1/2"	2-3/4"	3"	3-1/4"	3-1/2"	3-3/4"	4"	5"	6"	C _{ac}
3/8	12	4	7	7-1/8	Cracked (SD)	1,640	1,720	1,805	1,895	1,980	2,070	2,160	2,255	2,350	2,450	2,855	3,185	3,185
					Uncracked (SD)	2,675	2,805	2,935	3,075	3,210	3,350	3,495	3,645	3,790	3,945	4,580	5,260	6,240
					Uncracked (ASD)	1,650	1,730	1,810	1,895	1,980	2,065	2,155	2,250	2,335	2,435	2,825	3,245	3,850
1/2	12	4	7	6-3/8	Cracked (SD)	-	-	2,125	2,210	2,295	2,380	2,470	2,555	2,645	2,740	3,120	3,520	3,665
					Uncracked (SD)	-	-	3,295	3,450	3,605	3,760	3,925	4,085	4,255	4,425	5,140	5,900	6,240
					Uncracked (ASD)	-	-	2,030	2,125	2,225	2,320	2,420	2,520	2,625	2,730	3,170	3,640	3,850
5/8	18	6-5/8	7	10-5/8	Cracked (SD)	-	-	-	3,895	4,010	4,130	4,250	4,370	4,495	4,620	5,130	5,670	8,305
					Uncracked (SD)	-	-	-	5,140	5,295	5,450	5,610	5,770	5,935	6,100	6,775	7,485	11,725
					Uncracked (ASD)	-	-	-	3,170	3,265	3,360	3,460	3,560	3,660	3,765	4,180	4,620	7,235
3/4	24	8-1/8	7	12-5/8	Cracked (SD)	-	-	-	-	-	4,855	4,975	5,095	5,215	5,340	5,845	6,370	10,250
					Uncracked (SD)	-	-	-	-	-	6,620	6,780	6,945	7,110	7,280	7,965	8,685	14,470
					Uncracked (ASD)	-	-	-	-	-	4,085	4,185	4,285	4,385	4,490	4,915	5,360	8,930

NOTES:

- QE-1 & QE-2 have an installation temperature range of 5° F to 104° F for structural applications.
- All Strength Design (SD) values listed are controlled by bond strength.
- Table represents performance at specific edge distance, hole diameter and embedment depth conditions.
- Table values reflect reduction for use in a Condition B application, where supplementary reinforcement is not present.
- Allowable tension loads calculated based on strength design provisions of IBC Section 1605.2 with the following assumptions:
 - Temperature range A: Maximum short term temperature = 176° F (80° C), Maximum long term temperature = 122° F (50° C)
 - f_c = 2,500 psi, normal-weight concrete.
 - Single anchor, vertically down with periodic special inspection and no seismic loading.
 - φ_t = 0.65 for dry concrete, with ASTM A193, Grade B7 threaded rod.
- For short term temperature exposure greater than 176° F (80° C) and up to 248° F (120° C), apply a reduction factor of 0.90 to the allowable tension load.
- For short term temperature exposure greater than 248° F (120° C) and up to 302° F (150° C), apply a reduction factor of 0.80 to the allowable tension load.
- Allowable Stress Design (ASD) loads based on ACI load combination - 0.9D + W / 0.6D + 0.6W, assuming dead load of 30% and wind load of 70% giving a weighted average (α) of 1.62.

FIRE CAULK

PRODUCT FEATURES:

Ready-to-use, Metacaulk® MC 150+ Firestop Sealant is a general fire-rated elastomeric sealant for construction joints and through penetrations.

The sealant cures upon exposure to the atmosphere to form a firestop seal, which prevents spread of fire, smoke and noxious gas and when properly installed, it provides up to 4-hour fire protection.

MATERIAL:

Refer to manufacturer's literature.

INSTALLATION:

Refer to manufacturer's literature.

CODE COMPLIANCE:

Refer to manufacturer's literature.

Part No.	Qty.
FCBALCOFIRESTOP	5 gal. Pail

